



Application

- Telecommunication Networks
- FTTX, FTTH
- LAN, WAN, CATV and MAN applications
- Fiber Communication Systems
- Data Processing Networks
- Industrial and Military applications

Features:

- Constructed from high quality connectors and fibers
- Semi-tight-buffer, easy strippable
- Connection easy to link properly
- High corrosion resistance and high interface performance
- Supplied with a test report detailing insertion and return loss
- UL standard connectors, comply with ROHS requirements

3D Testing for all premium pigtails

Technical specifications and ordering information

Parameter	Unit	Singlemode 12 Colors Pigtails
Connector type		SC UPC
Insertion Loss	dB	≤0.2
Return Loss	dB	≥50
Fiber type		G.657.A
Pigtail length	m	2
Buffer style	dB	Tight Buffer 900µm
Buffer Material		LSZH
Colors		Red, Green, Blue, Yellow, White, Grey, Brown, Violet, Turquoise, Black, Orange, Pink
Operating temperature	°C	from -40 to +75
Part number		PTSC9A2TL

PIGTAIL	CONNECTOR TYPE	FIBER TYPE	LENGTH	JACKET TYPE
PT	SC - SC UPC SCA - SC APC	9A - Singlemode 9/125 OS2 G657A	2 - 2m	TL - Tight Buffer LSZH

PT	SC	9A	2	TL
----	----	----	---	----

Explanation: SC singlemode 2m pigtail with tight buffer LSZH jacket